(12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(19) World Intellectual Property Organization International Bureau



(43) International Publication Date 15 July 2004 (15.07.2004)

PCT

(10) International Publication Number WO 2004/058605 A1

(51) International Patent Classification7:

(21) International Application Number:

PCT/NL2003/000898

B65G 47/14

(22) International Filing Date:

17 December 2003 (17.12.2003)

(25) Filing Language:

Dutch

(26) Publication Language:


English

(30) Priority Data: 1022267

24 December 2002 (24.12.2002) NL

- (71) Applicant (for all designated States except US): CFS WEERT B.V. [NL/NL]; De Fuus 8, NL-6006 RV Weert
- (72) Inventors; and
- (75) Inventors/Applicants (for US only): VAN HOOF, Jo-

- (81) Designated States (national): AE, AG, AL, AM, AT (utility model), AT, AU, AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN, CO, CR, CU, CZ (utility model), CZ, DE (utility model), DE, DK (utility model), DK, DM, DZ, EC, EE (utility model), EE, EG, ES, FI (utility model), FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG. MK, MN, MW, MX, MZ, NI, NO, NZ, OM, PG, PH, PL, PT (utility model), PT, RO, RU, SC, SD, SE, SG, SK (utility model), SK, SL, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.
- (84) Designated States (regional): ARIPO patent (BW, GH, GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM). European patent (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, TT, LU, MC, NL, PT, RO, SE, SI, SK, TR), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).



(54) Title: SUPPLY DEVICE

(S7) Abstract: Device for supplying articles (30) provided with a head (31) and a stick (32), such as follipops, to a further treatment station, such as a packaging machine, comprising: a supply station add to stick (32) at its circumference for accommodation of the sticks, which slits extend from the holes to the outer edge of the distribution disc and wherein the slits comprises. extending from the bottom up and situated at a downstream side and upstream side of the slit in direction of rotation, respectively, wherein the downstream edge runs at least almost in a vertical plane and at least almost up to the upper side of the distribution disc, and the upstream edge (54) at least an upper portion gives way with respect to the downstream edge in upstream direction.